

## 14.7mm Circle Active Area

## Application

 Wearable, VR Gloves Sensing, Pulse Detection (Medical), Sleeping Posture Monitoring and many others

## Feature

✓ Ultra-thin, Lightweight, textile-like softness, causing minimum interference with physical movement.



Order Code	Outline Drawing		
MF01A-N-221-A12	Outline Drawing		
INSPECTION ITEM	SPECIFICATION		
FORCE SENSITIVITY RANGE	30g∼4000g (0.3N∼39N)		
FORCE RESOLUTION	Continuous (Analog)		
STAND-OFF RESISTANCE (UNLOADED)	> 20MΩ		
FORCE REPEATABILITY (SINGLE PART)	2%		
FORCE REPEATABILITY (PART TO PART)	10%		
RESPONSE TIME	< 1ms		
LIFE CYCLE (WITHOUT FAILURE)	> 10 Million		
OPERATING TEMPERATURE	-30°C to + 60°C		
HIGH HUMIDITY STORAGE	+40°C, 95%RH x 96hrs		
HIGH TEMPERATURE STORAGE	+60°C x 120hrs		
LOW TEMPERATURE STORAGE	-30°C x 120hrs		

## **CONNECTOR OPTIONS**

Bare Tail	Female Contacts	Solder Tabs (pin)	Female Contact with Housing

Design and specifications presented here are for the standard parts only. Please kindly contact us for your special requests and ask for the current technical specifications before purchase and/or use.